

SoySeal

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

DISTRIBUTED BY C2 Products, Inc.
ADDRESS 15222 Herriman Blvd. Noblesville, IN
TRADE NAME The Bean
SYNONYMS Water-dispersed expelled soy oil for concrete/deck sealant

2. COMPONENTS AND HAZARD CLASSIFICATION

Contains expelled soy oil, nonionic surfactant, and water Patented formulation
Contains no chemicals subject to SARA 302 or 313 reporting.

3. PHYSICAL DATA

BOILING POINT (F) ng SPECIFIC GRAVITY 0.99 @ 73F
VAPOR DENSITY n/a MELTING POINT ng
SOLUBILITY IN WATER Dispersible - yellow milky emulsion VAPOR PRESSURE N/A
APPEARANCE AND ODOR Odor is of soybean oil, appears as yellow milky emulsion

4. FIRE AND EXPLOSION DATA

FLASH POINT >500F (PM) AUTOIGNITION TEMPERATURE >500F
(TEST METHOD)
EXTINGUISHING MEDIA Foam, dry chemical, carbon dioxide, sand/earth
SPECIAL FIRE FIGHTING PROCEDURES None
UNUSUAL FIRE AND None expected.
EXPLOSION HAZARD None

5. HEALTH HAZARD INFORMATION

SLIPPAGE Slippery, may cause falls if walked on.
FIRST AID
EYES: Flush eyes with large amounts of water for at least 15 minutes. Seek medical aid.
SKIN: Remove contaminated clothing. Wash with soap and water. If irritation occurs, seek medical attention.
INHALATION: Remove to fresh air. If not breathing, give artificial respiration and seek medical attention immediately.
Oxygen should only be administered by trained personnel.
INGESTION: If swallowed, call a physician. ONLY induce vomiting at the instruction of a physician.
Never give anything by mouth to an unconscious person.
NATURE OF HAZARD:
EYE: Irritation may occur with exposure to concentrated vapors or contact with product. May cause corneal inflammation.
SKIN: Repeated or prolonged contact may cause reddening and scaling of the skin (dermatitis) if hypoallergenic.
INHALATION: This material is a negligible hazard due to its low volatility. If vapor is present in high concentrations, irritation to upper respiratory tract may occur.
INGESTION: Low order of toxicity. No hazard by this route in normal use. Ingestion of large amounts maybe irritating to gastrointestinal tract.
EXPOSURE LIMITS None established for this product.
TOXICITY DATA This product has not been specifically tested.

6. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY:

Stable under normal conditions for 12 months. Reacts slowly with air or oxygen. Heating increases oxidation potential.

INCOMPATIBILITY: Can react with strong oxidizers, inorganic acids, and halogens.

HAZARDOUS DECOMPOSITION PRODUCTS: None known.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: Should not occur.

7. SPILL OR LEAK PROCEDURES

Dike and contain the spilled material. Floor will be extremely slippery. Collect liquid with an inert absorbent and transfer to a container for reuse or disposal.

WASTE CLASSIFICATION: If discarded in its purchased form, this product is not a RCRA hazardous waste. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, and mixtures may change the classification.

8. SPECIAL PROTECTION INFORMATION

VENTILATION RECOMMENDATIONS Use only with adequate ventilation.

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

EYES: Chemical safety glasses.

SKIN: Use rubber or plastic, solvent resistant gloves.

RESPIRATORY PROTECTION: Use organic vapors mask when handling this product above 120 degrees F.

9. SHIPPING, TRANSFER AND STORAGE

SHIPPING INFORMATION

ICAO/IATA DESCRIPTION: This product is not a dangerous good as defined by IATA for air transportation.

DOT DESCRIPTION: Non hazardous liquid

TRANSPORTATION AND STORAGE

ELECTROSTATIC ACCUMULATION HAZARD: Precautions should be taken to prevent electrostatic discharge.

USUAL SHIPPING CONTAINERS: Tank cars, tank trucks, and drums, pails.

STORAGE/TRANSPORT TEMPERATURE: Ambient

STORAGE/TRANSPORT PRESSURE: Ambient

VISCOSITY: >15 cSt @ 100F

BULK QUANTITIES: Provide diking to contain potential spills.

HANDLING AND STORAGE MATERIALS AND COATINGS

TANKS: Use containers that will not rust. This is a water-based product.

THE ABOVE DATA IS BASED ON TESTS AND EXPERIENCE WHICH C2 PRODUCTS. (C2) BELIEVES RELIABLE AND ARE SUPPLIED FOR INFORMATIONAL PURPOSES ONLY. C2 PRODUCTS, INC. PRODUCTS ARE INTENDED FOR SALE TO AGRICULTURAL AND COMMERCIAL CUSTOMERS. C2 REQUESTS THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. C2 DISCLAIMS ANY LIABILITY FOR DAMAGE OR INJURY WHICH RESULTS FROM THE USE OF THE ABOVE DATA AND NOTHING CONTAINED THEREIN SHALL CONSTITUTE A GUARANTEE, WARRANTY (INCLUDING WARRANTY OF MERCHANTABILITY) OR REPRESENTATION (INCLUDING FREEDOM FROM PATENT LIABILITY) BY C2 WITH RESPECT TO THE DATA, THE PRODUCT DESCRIBED, OR THEIR USE FOR ANY SPECIFIC PURPOSE, EVEN IF THAT PURPOSE IS KNOWN TO C2.